

Silicone Tube

closed cell smooth finish



Extruded silicone tube(Silicone Tube)

performances excellently from -53°C to $+220^{\circ}\text{C}$. It also provides good weathering, UV and Ozone resistance.,without turning yellow and turn hard in low temperature environment .This enables our product to deliver consistent performance in almost any environment.

Silicone Tube

Type Description	Extruded Silicone Tube	Test Method
CODE	/	
Hardness, Shore A	55-65A	ASTMD2240
Density,g/cm ³ ,+/-0.05	1.25/798pcf	ASTMD1056
Cell Structure	/	
Surface skin	smooth	
Transparency	Excellent	
Bubbles	Few	
Tempertaure Ranger,°C	-60--220	ASTMD1056
UV/ozone Resistance	Excellent	ASTMD1056
Dielectric Strength V/cm	> 10E11	ASTMD1056
Flame Resistance	Inflammable	
Color	Trasparant、 Red or as required	
OD,mm	1.5-70(0.06-2.8in)	
Continous Rolls ,m	< 100(328ft)	
ID,mm	1-60(0.04-2.4in)	UL94
Thickness,mm	>0.5(0.02in)	

Note: 1.the data is only for reference.

2.The information contained in this Data Sheet is intended to assist you in designing with Sanpu's products. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular purpose or that the results shown in this Data Sheet will be achieved by a user for a particular purpose. .

Sanpu Silicone